

TEXHYDE (Premier)

Leather Look with Textile Softness

PREMIER has been developed to meet the rigorous demands of hospital, contract, and institutional use.

PREMIER is formulated to meet the flammability requirements contained in the following specifications:

- Federal Specification AA-2950A (Supersede CCCA680a)
- NFPA 701, Small Scale Test
- NFPA 260 A, Class 1
- Boston Fire Code (BFD IX-1)
- Federal Aviation Administration FAR 25.853(b) & Appendix F Part 1 (a) (i) (ii) (v)
- Port Authority of NY & NJ
- California Fire Regulation (Bulletin 117 -Section E)
- Motor Vehicle Safety Standard No. 302
- UFAC Class 1
- BIFMA

TECHNICAL DATA

- Width: 54 inches
- Weight: 40 ounces per linear yard
- Roll Length: 30 yards
- Sulfide stain resistant
- Oil resistant
- -20 degree F. cold crack
- Anti static slip finish
- Ultraviolet resistant
- Mildew and bacteria resistant (ASTM G21-70 & G22-76)
- Heat sealable
- Excellent cleanability
- Excellent seam strength

ORDERS

When placing orders please indicate:

- 1) Grade - Premium Grade Expanded
- 2) Pattern Name - **Premier**
- 3) Pattern Number - BA 636
- 4) Color Name and Number